

Outflow and clogging of shape-anisotropic grains in hoppers with small apertures

C. J. O'Gara, O. Q. J. C. O'Gara, C. N. K. C. U. J. Q. W. T. C. J. O'Gara, U. O. Y. G. I. P. G. T., V. O. V. T. K. V. Y. G. N., V. O. D. 3/4 t / u. 3/4 p {k" and R. Stannarius

Abstract

Outflow of granular material through a small orifice is a fundamental process in many industrial fields, for example in silo discharge, and in everyday life. Most experimental studies of the dynamics have been performed so far with monodisperse disks in two-dimensional (2D) hoppers or spherical grains in 3D. We investigate this process for shape-anisotropic grains in 3D hoppers and discuss the role of size and shape parameters on avalanche statistics, clogging states, and mean flow velocities. It is shown that an increasing aspect ratio of the grains leads to lower flow rates and higher clogging probabilities compared to spherical grains. On the other hand, the number of grains forming the clog is larger for elongated grains of comparable volumes, and the long axis of these blocking grains is preferentially aligned towards the center of the orifice. We find a qualitative transition in the hopper discharge behavior for aspect ratios larger than E_6 . At still higher aspect ratios 48612 , the outflowing material leaves long vertical holes in the hopper that penetrate the complete granular bed. This changes the discharge characteristics qualitatively.

Soft Matter 2017, January